

AMENDMENTS TO THE CLAIMS

1. (Previously Amended) An RF data transfer system comprising:
means for detecting repetitive RF interference which occurs during RF data transfer intervals;
means, operative in response to periodicity and duration data obtained by said detecting means, for scheduling said RF data transfer during said intervals that avoid said interference; and
means for determining the most efficient of:
scheduling said RF data transfer during said intervals that avoid said interference; and
transmitting said RF data during said data transfer intervals and allowing forward error correction of a receiver to correct errors in said RF data transfer;
wherein said scheduling means includes means for shifting a time sequence of said RF data transfer to avoid said interference.

2. (Canceled)

3. (Original) The system of claim 1 wherein said interference is a radar signal.

4. (Canceled)

5. (Original) The system of claim 1 wherein a modulation of said RF data transfer is changed to accommodate said time sequence shifting.

6. (Original) The system of claim 1 wherein a code rate of said RF data transfer is adjusted to accommodate said time sequence shifting.

7. (Original) The system of claim 1 wherein said scheduling means includes means for skipping at least one time slot in a sequence of time slots of said data transfer to avoid said interference.

8. (Previously Presented) The system of claim 7 wherein a modulation of said RF data transfer is changed to accommodate said skipping at least one time slot.

9. (Previously Presented) The system of claim 7 wherein a code rate of said RF data transfer is adjusted to accommodate said skipping at least one time slot.

10. (Original) The system of claim 1 wherein said means for detecting is an antenna separate from antennas used to effect said RF data transfer.

11. (Original) The system of claim 10 wherein said antennas used to effect said RF data transfer are sectorized and are used to determine a direction of said interference.

12 – 19. (Canceled)

20. (Previously Presented) A method for detecting and mitigating interference with RF data transmissions in certain RF bands, said method comprising the steps of:

determining time periods of repetitive RF interference within an RF band of interest, using at least one antenna in electrical communication with at least one RF filter, to arrive at an interference profile of periodicity and duration of said interference, wherein said at least one antenna is separate from antennas used to carry out said RF data transmissions; and

determining the most efficient of:

adjusting a time sequence of desired RF data transmissions to accommodate said interference profile, rescheduling transmissions to avoid said interference; and
transmitting said RF data and resending said data sent during said interference.

21. (Original) The method of claim 20 wherein a modulation of said RF data transfer is changed to accommodate adjustment of said time sequence.

22. (Original) The method of claim 20 wherein a code rate of said RF data transfer is adjusted to accommodate adjustment of said time sequence.

23. (Original) The method of claim 20 wherein said certain RF bands are unlicensed bands.

24. (Original) The method of claim 20 wherein said interference is a radar signal.

25. (Original) The method of claim 20 wherein said desired RF data transmissions occur in sequential repetitive time slots and wherein said adjusting step includes the step of eliminating at least one of said time slots for the duration of said interference.

26. (Previously Presented) The method of claim 25 wherein a modulation of said RF data transfer is changed to accommodate data in remaining ones of said time slots.

27. (Original) The method of claim 26 wherein a code rate of said RF data transfer is adjusted to accommodate remaining ones of said time slots.

28. (Original) The method of claim 20 wherein said at least one RF filter further comprises an RF detector.

29. (Original) The method of claim 20 wherein antennas used to effect said RF data transmissions are sectorized and are used to determine a direction of said interference.

30. (Canceled)

31. (Previously Presented) The system of claim 1 wherein efficiency is based on one or more of payload, customer payload, and data payload.

32. – 33. (Canceled)

34. (Canceled).

35. (Previously Presented) The method of claim 20 wherein efficiency is based on one or more of payload, customer payload, and data payload.

36. (Previously Presented) The system of claim 1 wherein said means for determining further determines whether transmitting said RF data during said data transfer intervals and resending data sent during said RF interference is more efficient than said scheduling said RF data transfer during said intervals that avoid said interference and said transmitting said RF data during said data transfer intervals and allowing forward error correction of a receiver to correct errors in said RF data transfer.

37. (Previously Presented) The method of claim 20 wherein said determining the most efficient further comprises determining whether transmitting said data and allowing forward error correction of a receiver to correct errors in said RF data transfer is more efficient than said adjusting a time sequence of desired RF data transmissions to accommodate said interference profile, rescheduling transmissions to avoid said interference, and said transmitting said data and allowing forward error correction of a receiver to correct errors in said RF data transfer.